

SAFETY AND BUILDINGS DIVISION
Plumbing Product Review
P.O. Box 2658
Madison, Wisconsin 53701-2658
TTY: Contact Through Relay

Jim Doyle, Governor Richard J. Leinenkugel, Secretary

July 2, 2009

CUSTOM CARE WATER TECHNOLOGIES INC. DANIEL M. PETERS 9087 WESTPHAL LANE NEENAH WI 54956

Re: Description: WATER TREATMENT DEVICE- SOFTENER Manufacturer: CUSTOM CARE WATER TECHNOLOGIES INC.

Product Name: CUSTOM SOFT SERIES 1500 (POE)

Model Number(s): 1522, 1523, 1532, 1533, 1542, 1543, 1552, 1553, 12512 AND 12513 (POE)

Product File No: 20090219

The specifications and/or plans for this plumbing product have been reviewed and determined to be in compliance with chapters Comm 82 through 84, Wisconsin Administrative Code, and Chapters 145 and 160, Wisconsin Statutes.

The Department hereby issues an approval based on the Wisconsin Statutes and the Wisconsin Administrative Code. This approval is valid until the end of July 2014.

This approval supersedes the approval issued on June 23, 2004 under product file number 20040284.

This approval is contingent upon compliance with the following stipulation(s):

- This product has undergone sufficient testing to document the product's ability to reduce only those contaminants and/or substances as specified in this approval letter when the product is installed and maintained in strict accordance with the manufacturers published instructions.
- Where the Department of Natural Resources (DNR) has jurisdiction, a written approval may be required prior to installation of this product in a water supply system to reduce the concentration of a contaminant that exceeds the primary drinking water standards contained in ch. NR 809, Wis. Admin. Code, the enforcement standards contained in ch. NR 140, Wis. Admin. Code, or for a water supply system that is subject to a written advisory opinion by the DNR. For more information contact the DNR Section of Private Water Systems, P.O. Box 7921, Madison, WI 53707, telephone (608) 266-3415.
- If these approved devices are modified or additional assertions of function or performance are made, then this approval shall be considered null and void, unless the change is submitted to the department for review and the approval is reaffirmed.
- These cation exchange water softeners shall be sized, installed, programmed and maintained such that wastewater volumes, total dissolved solids and chloride discharges are minimized.
- Operation of this/these device(s) and flow rates above the rated service flow rates indicated within this approval letter are not supported or acknowledged by this approval. The rated service flow rate(s) is/are the flow rate(s) at which this/these device(s) were tested.

Because the level of treatment obtained is a function of how long the water is in contact with the treatment media within this/these device(s), arbitrary increases in the flow rate(s), above the rated service flow rate(s) may compromise the quality of the treated water.

Based on testing data submitted to and reviewed by the department, this approval recognizes that these plumbing products will reduce the concentration of contaminants as specified on pages 1 through 2 of this letter.

SBD-10564-E (N.10/97) File Ref: 09021901.DOC

Custom Care Water Technologies Inc.

July 2, 2009 Page 2 of 2

Product File No.: 20090219

WATER SOFTENING CAPABILITIES PRODUCT FILE NUMBER 20090219 TABLE 1 OF 1

| Model Numbers | Capacity* | | | | | | Flow Rate vs. |
|---------------|-----------|--------|----------|--------|----------|--------|---------------|
| Series 1500 | Rating 1 | | Rating 2 | | Rating 3 | | Pressure Loss |
| Metered | Grains | Pounds | Grains | Pounds | Grains | Pounds | gpm @ psig |
| 1522 | 10,973 | 2.3 | 18,598 | 6.8 | 25,478 | 11.3 | 8.7 @ 14.9 |
| 1523 | 10,973 | 2.3 | 18,598 | 6.8 | 25,478 | 11.3 | 8.7 @ 14.9 |
| 1532 | 14,631 | 3.0 | 29,361 | 9.0 | 33,825 | 15.0 | 10.1 @ 15.0 |
| 1533 | 14,631 | 3.0 | 29,361 | 9.0 | 33,825 | 15.0 | 10.1 @ 15.0 |
| 1542 | 18,289 | 3.8 | 36,701 | 11.3 | 42,281 | 18.8 | 11.3 @ 14.9 |
| 1543 | 18,289 | 3.8 | 36,701 | 11.3 | 42,281 | 18.8 | 11.3 @ 14.9 |
| 1552 | 21,947 | 4.5 | 44,042 | 13.5 | 50,738 | 22.5 | 10.2 @ 15.0 |
| 1553 | 21,947 | 4.5 | 44,042 | 13.5 | 50,738 | 22.5 | 10.2 @ 15.0 |
| 1562 | 29,262 | 6.0 | 58,722 | 18.0 | 67,650 | 30.0 | 13.2 @ 15.0 |
| 1563 | 29,262 | 6.0 | 58,722 | 18.0 | 67,650 | 30.0 | 13.2 @ 15.0 |

^{*} The softener capacity rating is based on grains of hardness, due to calcium and magnesium cations, removed (as calcium carbonate) while producing soft water between successive regenerations and is related to the pounds of salt required for each regeneration. The tests run to generate the data for table 1 were conducted in accordance with NSF Standard 44.

This device was tested under controlled laboratory, or field, conditions. The actual performance of this device for a specific end use installation will vary from the tested conditions based on local factors such as water pressure, water temperature and water chemistry.

The department is in no way endorsing this product or any advertising, and is not responsible for any situation which may result from its use.

Sincerely,

Glen W. Schlueter
Engineering Consultant-Plumbing Product Reviewer
Bureau of Integrated Services
Safety and Buildings Division
Department of Commerce
(608) 267-1401 **Phone**(608) 267-9566 **Fax**glen.schlueter@wi.gov **Email**8:00AM – 4:30PM CDT **Work Hours**

GWS:gws